



designed to be different

Product specification Virtuo 80/2 and Virtuo 80/3 *)

Model name	Virtuo 80/2 two sided Virtuo 80/3 three sided
Description	Virtuo 80/2 Build in electric fire. Two sided fire view, minimal frame. Seamlessly built in possible. Robust wood logs. Realistic projected flame picture, several flame pictures possible. Eco Glow, with LED glowbed. Low output, 2 power levels available. Virtuo 80/3 As Virtuo 80/2, but with three sided fire view.
Purpose	Ambience and heating
Type of appliance	Build in fire
Electric Power level	0, 1 and 2 kW.
Flame picture (as of Q2-2022)	Standard available <ul style="list-style-type: none"> • Gentle • Graceful • Magic • Elegant Downloadable <ul style="list-style-type: none"> • Crackling • Dazzling • Rustic • Comfort • Dynamic • Disco • Relax • Christmas
Sizes	Virtuo 80/2 Engine: WxHxD = 842x1000x510mm Build in plaster trim: WxHxD = 842x558x399mm Fire View: WxHxD = 788x550x350mm Virtuo 80/3 Engine: WxHxD = 880x1000x510mm Build in plaster trim: WxHxD = 880x558x399mm Fire View: WxHxD = 788x550x350mm Bottom of build in frame: min. 137mm
Removal of heat	Natural draught. Additional ventilation not necessary. The appliance is supplied with a fan to spread the heat produced by the heating element.
Control	<ul style="list-style-type: none"> • Power level manually controlled by remote control, or • Thermostatic controlled using the app, or • Thermostatic controlled Time Schedule, with 4 switch points per day, 7 days per week, only available within the app. • The temperature sensor necessary for the thermostatic control is placed on the circuit board under the left upstanding beam of the unit.
Operation	<ul style="list-style-type: none"> • Infrared remote control, battery operated (2x battery AAA). With this it's possible to; <ul style="list-style-type: none"> ○ Switch the complete fire on / off ○ Switch between various pictures ○ Switch between Power level 0 (off), 1 and 2 kW ○ Switch sound on / off. • 0/I button on appliance top right corner • External control via app. The first time connection is made between the device and the local Wi-Fi network via bluetooth. After that, all communication is via Wi-Fi. This makes it possible to: <ul style="list-style-type: none"> ○ turn the device on / off, ○ influence the frequency and light intensity of the glow bed, ○ switch between different images, ○ pause the image, ○ turn off the image, and then show only the glow bed ○ download new images in the future, ○ regulate the capacities (see Control) ○ switch sound (on / off).
Electrical connection	230VAC with earth connection. Delivery in UK with UK-plug.
Accessories	• Convection spoiler for optimal warm air flow
Weight	Engine incl. packaging: 100 kg
Including	Wood logs, black and grey chips, black, grey and red stones, remote control, batteries, mains wire + plug (EU and UK) L=100cm, levelling feet



designed to be different

Special features	<ul style="list-style-type: none">• Very low power levels possible.• Various ambience settings, flame pictures and alternative pictures.• Sound included in several flame pictures.• Can be built in into the corner seamlessly.• Can be built in without build-in frame.• Minimum heat transfer, resulting in a maximum choice of contiguous materials.
CE-ID (PIN)	Not applicable for electric fires.

		Unit
Nominal heat output	2	kW
Minimum heat output (indicative)	1	kW
Maximum continuous heat output	2	kW
Auxiliary electricity consumption:		
• At nominal heat output	40	W
• At minimum heat output	40	W
• In standby mode	<0.5	W

*) Consult installation manual for details.

Modifications review

Date	Nature of modification
17-03-2020	New specification.
23-03-2020	Dimensions build in frame corrected
08-05-2020	Weight adjusted
09-10-2020	Information about app added
21-10-2021	Adjustment of available flame pictures
29-3-2022	Adjustment of available flame pictures