Declaration of performance according to Regulation (EU) 305/201

Information according to (EU) 305/2011	**Registration by the manufacturer**
Unique identification code of the product type	Classic
Intended use(s)	Space heating in residential buildings
Manufacturer / trade mark	Westbo of Sweden AB Industrigatan 8, 333 75 Reftele SWEDEN
E-Mail	info@westbo.net
Authorised representative	Westbo of Sweden AB Industrigatan 8, 333 75 Reftele SWEDEN
E-Mail	info@westbo.net
System(s) of assessment and verification of constancy of performance of the construction product	System 3
The notified test laboratory has performed the initial test according to system 3. Notified body(ies)	NB-1625 Rhein-Ruhr Feuerstätten Prüfstelle GmbH Im Lipperfeld 34b, 46047 Oberhausen, DEUTSCHLAND Test report number RRF – 40 10 2377-2
Harmonised technical specifications	EN 16510-2-1:2022
Essential characteristics	
Mechanical resistance and stability	
Load bearing capacity	80 kg
Safety in case of fire	
Protection of combustible materials	Minimum distance to combustible materials – bottom d_B = 0 mm
	Minimum distance to combustible materials – floor in front d_F = 560 mm
	Minimum distance to combustible materials – ceiling d_C = 750 mm
	Minimum distance to combustible materials – rear d_R = 150 mm
	Minimum distance to combustible materials – side d_S = 300 mm
	Minimum distance to combustible materials – side radiation area d_L = 560 mm
	Minimum distance to adjacent combustible materials – front radiation area d_P = 800 mm
	Material type and thickness of the protective insulation material s = 0 mm
Hygiene, health and environment	
Emissions at nominal heat output	
Carbon monoxide (CO)	1500 mg/m³
Nitrogen oxides (NO_x)	200 mg/m³
Organic gaseous carbon (OGC)	120 mg/m³

Westbo of Sweden

Particulate matter (PM)	40	mg/m³
Emissions at part load heat output		
Carbon monoxide (CO)	NPD	mg/m³
Nitrogen oxides (NO_x)	NPD	mg/m³
Organic gaseous carbon (OGC)	NPD	mg/m³
Particulate matter (PM)	NPD	mg/m³
Information according to (EU) 305/2011	**Registration by the manufacturer**	
Safety and accessibility in use		
Data for installation to a chimney at nominal heat output		
Flue gas outlet temperature	305	°C
Minimum flue draught	12	Pa
Flue gas mass flow	5,3	g/s
Data for installation to a chimney at part load heat output		
Flue gas outlet temperature	NPD	°C
Minimum flue draught	NPD	Pa
Flue gas mass flow	NPD	g/s
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T600 - G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal heat output		
Space heat output	7,0	kW
Water heat output	NPD	kW
Efficiency	81	%
Appliance's thermal output and energy efficiency at part load heat output		
Space heat output	NPD	kW
Water heat output	NPD	kW
Efficiency	NPD	%
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output	65	%
Energy Efficiency	Energy Efficiency Index (EEI)	107
	Energy efficiency class	A+
Electric power consumption at nominal heat output	NPD	kW
Electric power consumption at part load heat output	NPD	kW
Power consumption in standby mode	NPD	kW
Sustainable use of natural resources		
Environmental sustainability	NPD	

The performance of the product identified above is in conform ity with the set of declared performance.

This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer

Mattias Gunnarsson, CEO
Westbo of Sweden AB
2026-02-18

Westbo of Sweden